

TRS21E

Spark-less ignition proof 240v
 A1 A2/L A3 compatible recovery



Refrigerant Recovery Machine

A-Class Refrigerant Suitable

KEY FEATURES

- Designed and tested to meet ANSI 12:12.01 Ignition Proof standards
- For use on refrigerant systems utilizing Class A1, R-32, R-1234yf and R-1234ze, R600, R290 and more.
- Maintenance free oil-less compressor
- Permanently lubricated and sealed main bearings
- Improved piston seal design for less leakage and deeper vacuums
- High pressure cut-off switch with LED indicator
- Cleanable 100 mesh inlet filter
- Fastest recovery rates in its class
- Ignition proof ON-OFF switch
- Sealed start relay
- Hard wired 9.8 ft. (3m) power cord
- CE, TUV listed
- 1 Year Warranty
- Lightweight only 11 Kg

DESCRIPTION

An efficient, lightweight and reliable recovery machine, that meets ANSI ignition proof standards. This compact rugged design is an ideal combination of form and function. TRS21 will make recovery faster and easier!

| Recovery Method | R410A | R22 | R134A |
|------------------|------------------------------|--------------------------------|--------------------------------|
| Direct Vapor | 0.703 lb/min 0.319 kg/min | 0.597 lb/min (0.271 kg/min) | 0.503 lb/min (0.228 kg/min) |
| Direct Liquid | 11.95 lb/min 5.42 kg/min | 8.86 lb/min (4.02 kg/min) | 7.8 lb/min (3.54 kg/min) |
| PUSH/PULL Liquid | 31.7 lb/min 14.38 kg/min | 31.53 lb/min (14.3 kg/min) | 25.66 lb/min (11.64 kg/min) |

SPEED-UP RECOVERY



MT69 - SUB COOLER


TRS21E

Spark-less ignition proof 240v
A1 A2/L A3 compatible recovery

Refrigerant Recovery Machine from cps®

The CPS TRS21E is a spark-less, ignition-proof with fully insulated on/off switch refrigerant recovery machine. This unit does away with traditional components that cause possible points for refrigerant to escape making it more convenient for the Engineer when handling mildly- flammable refrigerants.

LIGHTWEIGHT. ROBUST. PATENTED DESIGN.
A-CLASS REFRIGERANTS SUITABLE



| Model | TRS21E | |
|----------------------------------|--|-----------|
| Voltage (Hz) | 115V 60Hz | 230V 50Hz |
| Motor Size | 2/3 HP | |
| Motor Thermally Protected | Yes | |
| Compressor | 2 Cylinders Oil-less Reciprocating Compressor | |
| Power Consumption | 1000W | |
| High Pressure Shut-Off | 450 psig (Auto Reset) | |
| ARI740 CLASS III | R12, R134A, R401C, R406A, R500 | |
| ARI740 Class IV | R1234YF, R22, R410A/B, R402B, R407C/D/E/F, R408A, R409A, R411A/B, R412A, R502, R509A | |
| ARI740 Class V | R32, R402A, R404A, R407A/B, R410A/B, R507A | |
| ASHREA/ISO Class A2,/L, A3 Types | R1234YF, R32, R290, R600, R601, R1276 | |
| Operating Temperature Range | 0°C to 49°C (32°F to 120°F) | |
| Power Cord Length | 3m | |
| Dimensions | 15cm x 30cm x 23cm | |
| Weight | 11Kg | |
| Approvals | *UL, CSA | |

FOR UK-Based Spares & Repairs, contact your preferred CPS Stockist:-

CAPACITOR 460-552 UF 125 VAC

RED LED LIGHT 220V

IGNITION PROOF SWITCH

SW HI PRESSURE 80PS AUTO RESET 550

START RELAY 4CR-1-747 SEALED

SS FITTING INLET/DISCHARGE PORT

TRS21 FAN SHROUD

ELECTRICAL BOX COVER

HANDLE

FAN BLADE

Distributed by:
EVOMART
Unit 6 Jupiter House
Calleva Industrial Park
Aldermaston RG7 8NN
Tel: 0330 135 9922
evomart.co.uk



VIEW ONLINE
SCAN ME

 **EVOMART**
EVOLUTION IN DISTRIBUTION